

Faster - better - everywhere.





VX 8100.710 Levelling component

CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES

State: 21/07/2025 (Source: rittal.com/gr-en)

POWER DISTRIBUTION



FRIEDHELM LOH GROUP

ENCLOSURES

VX 8100.710 - Levelling component for base/plinth system VX

For retrospective levelling on uneven floors at the installation site up to a maximum of 15 mm. Installed through the base/plinth corner piece.

Features

Model No.	VX 8100.710
Product description	For retrospective levelling on uneven floors at the installation site up to a maximum of 15 mm. Installed through the base/plinth corner piece. Adjusted using a SW 19 hex spanner.
Benefits	A door offset caused by uneven flooring can be corrected Installed on the assembled enclosure, i.e. no need to plan levelling in advance
Supply includes	Assembly parts
Load capacity	Max. admissible load: 2500 N per levelling component
Note	For use in combinations of VX, VX IT, VX SE, TX , TS, TS IT, PC, IW, TP with the base/plinth system VX Check the load capacity of the floor.
Dimensions	Height: 100 mm
Weight/pack	0.74 kg
Packs of	4 pc(s).
Net weight	0.68
Gross weight	0.74
Customs tariff number	73181900
EAN	4028177921559
ETIM 9	EC000721
ECLASS 8.0	27182003