
Rittal – The System.

Faster – better – everywhere.





IT INFRASTRUCTURE SOFTWARE & SERVICES

TS 8802.165 Section for cable entry, rear

CLIMATE CONTROL

State: 06/09/2025 (Source: rittal.com/gr-en)

POWER DISTRIBUTION



FRIEDHELM LOH GROUP

ENCLOSURES

TS 8802.165 - Section for cable entry, rear for TS, TP

For mounting directly onto the base opening.

Features

Model No.	TS 8802.165
Product description	For sealing the cable entry at the base opening.
Benefits	Particularly well-suited to cables with identical cross-sections When installing the mounting plate in the rearmost position, the cables may be routed directly with no large radii.
Technical specifications	Foam rubber cable clamp strip: Cross-section: 30 x 25 mm
Applications	Mount directly on the base opening/base tray and gland plate
Material	Extruded aluminium section Foam rubber cable clamp strip: PU foam
Supply includes	Plug-in sections, incl. foam rubber clamp strip
Note	2 pc(s). are sufficient for one base opening up to an enclosure width of 800 mm From an enclosure width of 1000 mm, two base openings are provided. 4 packs per enclosure may be fitted
To fit	Enclosure type: TS: = 1,600 mm Enclosure type: TP
IP protection category to IEC 60 529	IP 55 if installed correctly
Packs of	4 pc(s).
Net weight	0.592
Gross weight	0.6
Customs tariff number	76042990
EAN	4028177556836
ETIM 9	EC002624
ECLASS 8.0	27189265