

Faster – better – everywhere.





VX 8828.000 Bayed enclosure system VX25

IT INFRASTRUCTURE SOFTWARE & SERVICES

State: 05/09/2025 (Source: rittal.com/gr-en)

POWER DISTRIBUTION >> CLIMATE CONTROL



FRIEDHELM LOH GROUP

ENCLOSURES

VX 8828.000 - Bayed enclosure system VX25 Basic enclosure

The standard in enclosure manufacturing: Enclosure frame with one or two front doors, rear panel, mounting plate, roof plate, divided gland plates. Perfectly suited to efficient enclosure interior installation.



Features

Model No.	VX 8828.000
Material	Enclosure frame: Sheet steel, 1.5 mm
	Roof: Sheet steel, 1.5 mm
	Door: Sheet steel, 2.0 mm
	Rear panel: Sheet steel, 1.5 mm
	Gland plates: Sheet steel, 1.5 mm
	Mounting plate: Sheet steel, 3.0 mm
Surface finish	Enclosure frame: Dipcoat-primed
	Door, roof and rear panel: Dipcoat-primed, powder-coated on the
	outside, textured paint
	Mounting plate and gland plates: Zinc-plated
Colour	RAL 7035

Features

Supply includes	Enclosure frame
	Door(s)
	Door hinged on the right, may be swapped to the left Roof plate
	Rear panel
	Gland plates
	Mounting plate
	2 punched rails 18 x 39 mm
	Lock: 3 mm double-bit
Dimensions	Width: 800 mm
	Height: 2,200 mm
	Depth: 800 mm
Dimensions mounting plate (W x H)	699 mm x 2,096 mm
Protection category to IEC 60 529	IP 55
Protection category NEMA	NEMA 12
Type rating to UL 50E	Туре 1
	Type 12
IK Code	IK10
Number of doors	1
Basic material	Sheet steel
Packs of	1 pc(s).
Net weight	298.501
Gross weight	323.633
PCF per pack (cradle-to-gate)	362.2 kg CO2 eq (Cat B)
Note on PCF category	Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared
Customs tariff number	8421399090
EAN	4028177935990
EAN11 (UC)	94010
ETIM 9	EC000261

Features

ETIM 8	EC000261	
ECLASS 8.0	27180101	
Approvals		
Approvals	UL + C-UL (listed)	
Certificates	Surface finish	
Explanations	Manufacturer's declaration Declaration of conformity Declaration of conformity UK PCF-declaration	