

Rittal – The System.

Faster – better – everywhere.



SV 9342.510

Circuit-breaker component adaptor

State: 05/04/2026 (Source: rittal.com/gr-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SV 9342.510 - Circuit-breaker component adaptor 3-pole

Circuit-breaker adaptor for universal, simplified assembly of circuit-breakers.

Features

| | |
|---|---|
| Model No. | SV 9342.510 |
| Material | Polyamide Fire protection corresponding to UL 94-V0 |
| Colour | RAL 7035 |
| Supply includes | Terminal cover Sliding blocks |
| Type of electrical connection | Box terminal |
| Rated current max. | 160 A |
| Rated operating voltage | 690 V, 3~ |
| Cable outlet | Bottom |
| For bar systems with centre-to-centre spacing | 60 mm |
| Note | Cable outlet: Switch outlet or as outgoing cable from the switchgear The technical data may vary for UL applications |
| Number of poles | 3-pole |
| Dimensions | Width: 90 mm Height: 215 mm |
| Connection of round conductors | 35 - 120 mm ² |
| To fit busbars | Height: 5, 10 mm |
| Clamping area for laminated copper bars (W x H) | 18.5 x 15.5 mm |

Features

| | |
|------------------------------|--|
| To fit manufacturer (model) | ABB (S1, S2, T1, T2, XT1, XT2) Allen Bradley (140-CMN) Eaton (NZM1, BZM B1) GE (FD160) Legrand (DPX 125, DPX 160) OEZ (BC160N) Schneider Electric (NS80, NSC100) Schrack (MC1) Siemens (3RV13 53, 3VT1, 3VA10, 3VA11) Terasaki (E125, S125) |
| Packs of | 1 pc(s). |
| Net weight | 0.778 kg |
| Gross weight | 0.82 kg |
| Copper weight (kg per piece) | 0.202 |
| Customs tariff number | 85369095 |
| ETIM 9 | EC001531 |
| ECLASS 8.0 | 27370304 |
| Product description | SV Circuit-breaker component adaptor, 160 A, 690 V, 3-pole, cable outlet bottom, round conductor connection 35-120 mm ² , clamping area WH: 18,5x15,5 mm |

Approvals

| | |
|--------------|---|
| Approvals | ABS DNV-GL Lloyds Register of Shipping |
| Explanations | Declaration of conformity Declaration of conformity UK |

Tender text

Circuit-breaker component adaptor 160 A
CB component adaptor up to 160 A, 3 pole,
cable outlet at the bottom
for busbar thickness 5/10 mm and PLS 800/1600

Type of connection

Box terminal: Round conductor 35 - 120 qmm

Clamping area for laminated copper bar:

18.5 x 15.5 mm

Technical specifications

Construction width: 90 mm

Length: 215 mm

Electrical parameters

Rated current: up to 160 A

Rated operating voltage Ue: AC 690 V

System:

Rittal RiLine60