



Rittal – The System.

Faster – better – everywhere.



SV 9345.100 Fuse holders

State: 30/08/2025 (Source: rittal.com/gr-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SV 9345.100 - Fuse holders 61 A to 400 A

3-pole, for busbar systems with 60 mm bar centre distance.

Features

| | |
|---|--|
| Model No. | SV 9345.100 |
| Design | For category J fuse type |
| Material | Polyamide Fire protection corresponding to UL 94-V0 Contact tracks: Electrolytic copper, silver-plated |
| Colour | Chassis: RAL 7035 Cover: RAL 7035/7001 |
| Connection for round conductor | AWG 2 – MCM 300 |
| For bar systems with centre-to-centre spacing | 60 mm |
| Cable outlet | Top/bottom |
| Type of electrical connection | Box terminal |
| For fuse type (class) | J |
| Rated operating current max. | 100 A |
| Rated operating current (min.) | 61 A |
| Rated operating voltage | 600 V, 3~ |
| Fuse standard | UL 248-8 |
| Note | UL (listed accessory) is met when using the fuse holder on RiLine busbar systems |
| Standards | UL 508 |
| Dimensions | Width: 184 mm Height: 288 mm |
| To fit fuses | Diameter: 29 mm Length: 118 mm |
| To fit busbars | Height: 5, 10 mm |

Features

| | |
|------------------------------|---|
| Electrical ratings UL (SCCR) | 100 kA - 600 V, Fuse Class J max. 100 A, JDDZ/7 |
| Number of poles | 3-pole |
| Packs of | 1 pc(s). |
| Net weight | 2.61 |
| Gross weight | 2.615 |
| Copper weight (kg per piece) | 0.837 |
| Customs tariff number | 85366990 |
| EAN | 4028177615656 |
| ETIM 9 | EC001644 |
| ECLASS 8.0 | 27400613 |

Approvals

| | |
|-----------|--|
| Approvals | C-UR UL + C-UL (listed) UR + C-UR (recognized) |
|-----------|--|

Tender text

Fuse holder Class J, 61 - 100 A, 3-pole
for busbar thickness 5 / 10 mm and PLS 800 / 1600
Type of connection
Box terminal, round conductor AWG 2 - MCM 300
System:
RiLine Class