

**Rittal – The System.**

Faster – better – everywhere.



**SV 9677.380**

**NH slimline switch-disconnector**

State: 11/01/2026 (Source: [rittal.com/gr-en](http://rittal.com/gr-en))



FRIEDHELM LOH GROUP

# SV 9677.380 - NH slimline switch-disconnector with electronic fuse monitoring

3-pole, for bar systems with 185 mm centre-to-centre spacing.

## Features

Model No.	SV 9677.380
Design	3-pole, switchable
Function principle	Automatic quick-break contact allows operator-independent switching Double-break for reliable disconnection of the contacts
Material	Polyamide Fire protection corresponding to UL 94-V0 Contact tracks: Partially silver-plated hard copper
Colour	Chassis: RAL 7035 Cover: RAL 7001 Handle: RAL 7016
For NH size	3
For bar systems with centre-to-centre spacing	185 mm
Cable outlet	Bottom
Type of electrical connection	Screw M12
Installation type	Screw attachment
Number of poles	3-pole
Rated operating voltage	400 V, 3~
Rated operating current max.	630 A
Test specification	IEC/DIN EN 60 947-3 DIN EN 60 269-2 (fuse inserts)
Dimensions	Width: 100 mm Height: 941 mm

## Features

---

Connection of round conductors 6 - 240 mm<sup>2</sup>

To fit busbars Height: 10 mm

Packs of 1 pc(s).

Net weight 15.56

Gross weight 15.72

Copper weight (kg per piece) 4.78

Customs tariff number 85043129

EAN 4028177806825

ETIM 9 EC001040

ECLASS 8.0 27371401

## Approvals

---

Explanations

Declaration of conformity

Declaration of conformity UK