Rittal – The System.

Faster – better – everywhere.





SK 3237.400 Blue e+ outlet filter

State: 03.12.2025. (Source: rittal.com/hr-hr)



SK 3237.400 - Blue e+ outlet filter EMC

The outlet filter is used in conjunction with the corresponding fan-and-filter unit to dissipate heat loss from enclosures, ventilate the enclosure and protect temperature-sensitive components. This is achieved through the direct infeed of ambient air, the temperature of which must be lower than the permissible internal temperature of the enclosure.







Features

| SK 3237.400 |
|--|
| wall-mounted EMC |
| Easy filter changes, thanks to a new opening mechanism on the louvred grille Faster installation on the enclosure with optimised detent hooks Tool-free assembly |
| RAL 7035 |
| Outlet filter EMC filter mat |
| Cut-out width: 92 mm Cut-out height: 92 mm |
| SK 3237.8xx |
| Width: 116.5 mm Height: 116.5 mm Depth: 33.2 mm |
| |

© Rittal 2025 2

Features

| Protection category NEMA | Type 12 with chopped-fibre filter |
|----------------------------------|--|
| Trotoston outogory NEWIA | Type 3, 3R with chopped-fibre filter and hose-proof hood |
| IP protection category to IEC 60 | IP 54 with chopped-fibre filter |
| 529 | IP 56 with chopped-fibre filter and hose-proof hood |
| Packs of | 1 pc(s). |
| Net weight | 0.075 |
| Gross weight | 0.154 |
| Customs tariff number | 39269097 |
| EAN | 4028177998414 |
| ETIM 9 | EC002513 |
| ETIM 8 | EC002513 |
| ECLASS 8.0 | 27180706 |

Approvals

| Approvals | UL + C-UL - FTTA |
|-----------|------------------------|
| | UR + C-UR (recognized) |

© Rittal 2025 3