

Rittal – The System.

Faster – better – everywhere.



SK 3302.310

TopTherm wall-mounted cooling unit Blue e

State: 01.12.2025. (Source: rittal.com/hr-hr)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SK 3302.310 - TopTherm wall-mounted cooling unit Blue e 0.3 - 4 kW

Energy-efficient Blue e wall-mounted cooling units in the output categories 300 W to 4000 W and with integral electrical condensate evaporator (from 1000 W). Available in the special formats "horizontal" and "flat".



Features

| | |
|--------------------------------------|---|
| Model No. | SK 3302.310 |
| Design | wall-mounted Horizontal |
| Product description | Energy-efficient Blue e wall-mounted cooling units in the output categories 300 W to 4000 W and with integral electrical condensate evaporator (from 1000 W). |
| Benefits | May be linked to the IoT interface via Blue e IoT adaptor for cooling units from 500 W cooling output with e-Comfort controller |
| Material | Sheet steel |
| Colour | RAL 7035 |
| Supply includes | Condenser with hydrophobic RiNano coating Fully wired ready for connection (plug-in terminal strip) Drilling template Assembly parts |
| Total cooling output to DIN EN 14511 | Cooling output L35 L35/60 Hz: 0.32 kW Cooling output L35 L50/60 Hz: 0.16 kW |
| Rated operating voltage | 115 V, 1~, 60 Hz |
| Rated current max. | At 60 Hz: 4 A |

Features

| | |
|--|---|
| Start-up current max. | At 60 Hz: 12 A |
| Air throughput (unimpeded air flow) | External circuit: 300 m ³ /h Internal circuit: 300 m ³ /h |
| Energy efficiency ratio (EER) 50/60 Hz L35 L35 | Refrigeration factor L35 L35 (EER) 60 Hz: 1 |
| Design | wall-mounted |
| Special design | Horizontal |
| Dimensions | Width: 525 mm Height: 340 mm Depth: 153 mm |
| Protection category to IEC 60 529 | External circuit IP 34 Internal circuit IP 54 |
| Protection category NEMA | UL Type 12 |
| Refrigerant/cooling medium | Refrigerant: R-513A Quantity: 0.18 kg Global Warming Potential (GWP): 631 CO ₂ equivalent (CO ₂ e): 0.11 t |
| Temperature control | Basic controller (factory setting +35 °C) |
| Operating temperature range | 10 °C...55 °C |
| Storage temperature range | -40 °C...70 °C |
| Setting range | 30 °C...55 °C |
| Power consumption Pel | Power consumption L35 L35/60 Hz: 0.32 kW Power consumption L35 L50/60 Hz: 0.37 kW |
| Permissible operating pressure (p. max.) | 25 bar |
| Pre-fuse | Miniature circuit-breaker/fuse: 10 A |
| Packs of | 1 pc(s). |
| Net weight | 15.2 |
| Gross weight | 16 |
| Customs tariff number | 84158200 |

Features

| | |
|------------|---------------|
| EAN | 4028177429802 |
| ETIM 9 | EC000855 |
| ETIM 8 | EC000855 |
| ECLASS 8.0 | 27180704 |

Approvals

| | |
|-----------|--|
| Approvals | UL + C-UL (listed) UL + C-UL - FTTA UR + C-UR (recognized) |
|-----------|--|

| | |
|--------------|-----|
| Certificates | EAC |
|--------------|-----|

| | |
|--------------|---|
| Explanations | Declaration of conformity Declaration of conformity - F-gas regulation Declaration of conformity UK |
|--------------|---|