


Rittal – The System.

Faster – better – everywhere.



AS 4051.237

Wire rail WT

State: 11.05.2026. (Source: rittal.com/hr-hr)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AS 4051.237 - Wire rail WT

The pre-assembled wires are fed into the WT 53 wire rail with a cross-section of 6.0 mm² by the removal handling system.



Features

Model No.	AS 4051.237
Product description	Busbar clamber for Perforex machining centres BC and Perforex milling terminals MT, for simple machining of copper bars. Suitable for drilling and thread tapping.
Benefits	<ul style="list-style-type: none">Project-specific order picking for downstream processesProject-specific sorting of the wiresOptimum removal handlingBusbar system prepared for optimum workstation order-pickingNo wire sorting requiredSimplifies the wiring process with step-by-step instructions in Eplan Smart WiringIdeal in conjunction with the Wire Cart for perfect workstation order picking
Supply includes	Wire rail WT 53
Note	This gap size indicates the maximum diameter of the wire insulation.
To fit Model No.	4051.205 4051.210 4051.024 4051.036
Applications	For single wires with cross-section 6 mm ² (gap size 5.3 mm)
Packs of	1 pc(s).

Features

Net weight	0,85 kg
Gross weight	1 kg
Customs tariff number	76169990
Product description	Wire rail, 6.0 mm ² for the 15-way rail system in the WT
