

# Rittal – The System.

Faster – better – everywhere.



## AS 4052.107 Screwdrivers

State: 09.07.2026. (Source: [rittal.com/hr-hr](http://rittal.com/hr-hr))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# AS 4052.107 - Screwdrivers insulated

With a long, slender handle and high-performance tip with non-transfer insulation.

## Features

|                           |  |
|---------------------------|--|
| Model No.                 | AS 4052.107  |
| Design                    | Isolation protection 1000 V<br>for slot-head screws  |
| Product description       | With a long, slender handle and high-performance tip with non-transfer insulation.   |
| Benefits                  | Minimal force required, thanks to ergonomically styled handle<br>Handle head with anti-roll protection and clear screw labelling<br>Black coated blade tip to preserve precision and accuracy of fit<br>Handle 30% and insulation up to 50% slimmer than comparable tools<br>Optimum interconnection of hand and handle supports higher torques and longer, fatigue-free working |
| Material                  | Blade: Chrome-molybdenum-vanadium alloy<br>Handle core: Hard plastic<br>Handle body: Elastic, highly flexible plastic  |
| Colour                    | Handle: Anthracite and Rittal Power Pink   |
| Blade dia.                | 6,5 mm   |
| Blade length              | 125 mm   |
| Blade (width x thickness) | 6.5 x 1.2 mm   |
| Blade tip                 | SL   |
| Handle dia.               | 27 mm  |
| Handle length             | 115 mm   |
| Standards                 | IEC 60 900   |
| Packs of                  | 3 pc(s).   |
| Customs tariff number     | 82054000   |
| ETIM 9                    | EC000144   |

# Features

---

|                     |                                    |
|---------------------|------------------------------------|
| ETIM 8              | EC000158                           |
| ECLASS 8.0          | 21040406                           |
| Product description | Screwdriver insulated SL 6,5 x 1,2 |

---