

# Rittal – The System.

Faster – better – everywhere.



## DK 7320.792 Door kit

State: 18.12.2025. (Source: [rittal.com/hr-hr](https://www.rittal.com/hr-hr))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# DK 7320.792 - Door kit for Automatic Door Opening (ADO)

Gas pressure damper system, allowing the door to be opened in any emergency situation. The door kit is connected and activated using the corresponding door control module.

## Features

|                                   |   |
|-----------------------------------|---|
| Model No.                         | DK 7320.792   |
| Design                            | for two-piece door  |
| Product description               | For automatic opening of a rack's doors in emergency situations. Connected and activated via the Door Control Module.                                   |
| Function principle                | The doors are kept closed by a magnetic system. If the power supply to the magnets is interrupted, the gas pressure damper system pushes the door open. |
| Supply includes                   | with gas pressure damper system<br>Assembly parts   |
| Operating temperature range       | -5 °C...45 °C   |
| Ambient humidity (non-condensing) | 5...95 %  |
| Packs of                          | 1 pc(s).  |
| Net weight                        | 3.5   |
| Gross weight                      | 3.76  |
| Customs tariff number             | 73269098  |
| EAN                               | 4028177606173   |
| ETIM 9                            | EC001770  |
| ECLASS 8.0                        | 27390190  |

## Approvals

# Approvals

---

Explanations

Declaration of conformity

Declaration of conformity UK

## Tender text

Automatic Door Kit, 2-piece door  
Equipment kit for a door of a TS 8 rack type for the  
Automatic Door Opening System.

A door may be electro-mechanically equipped with the  
Automatic Door Kit for the Automatic Door Opening  
System.

The Automatic Door Kit operates with a gas pressure  
damper system, allowing the door to be opened in any  
emergency situation. The doors are kept closed by a  
magnet system, which unlike mechanical lock systems  
will release the door in every instance.

The kit is activated by the Automatic Door Control  
Unit. The feeding is 24 V / 400 mA.  
Cabling to the control unit is made via plug & play.

The Door Kit is suitable for glazed doors and solid  
sheet steel doors from Rittal or equivalent.

Approvals: CE

The Automatic Door Kit 7320.790 is additionally  
required for a complete system.