

# Rittal – The System.

Faster – better – everywhere.



## DK 7544.000 Earth rail, vertical

State: 13.07.2025. (Source: [rittal.com/hr-hr](https://www.rittal.com/hr-hr))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# DK 7544.000 - Earth rail, vertical for VX, VX IT

The supplied earth conductors facilitate star earthing of the cable clamp straps in the patch panels, the earth terminals are fully adjustable, current carrying capacity of rails approx. 200 A.

## Features

|                       |   |
|-----------------------|---|
| Model No.             | DK 7544.000   |
| Product description   | Easily fitted to the 25 mm DIN pitch pattern of distributors or to the 482.6 mm (19") mounting angles. The supplied earth conductors facilitate star earthing of the cable clamp straps in the patch panels. The earth terminals are fully adjustable. Current carrying capacity of rail approx. 200 A. |
| Supply includes       | Earth rail made from E-Cu 57 to DIN EN 12 163, DIN EN 13 601, 15 x 5 mm<br>null<br>15 earthing leads 6 mm <sup>2</sup> , L = 500 mm<br>Assembly parts   |
| Dimensions            | Length: 1,145 mm  |
| To fit                | Enclosure type: VX<br>VX IT<br>TS<br>Height: 1,400 mm   |
| Packs of              | 1 pc(s).  |
| Net weight            | 2.017   |
| Gross weight          | 2.217   |
| Customs tariff number | 74198090  |
| EAN                   | 4028177131859   |
| ETIM 9                | EC000329  |
| ECLASS 8.0            | 27400605  |

## Tender text

Earth rail for 1400 mm high network enclosures  
For the vertical installation in 1400 mm high  
network enclosures.

Earth rail made from E-Cu 57 (15 x 5 mm)  
to DIN 1759, DIN 40 500 is fitted to the  
482.6 mm (19 inch) mounting angles or to  
the 25 mm DIN 43 660 pitch pattern of distributors.

The supplied earth conductors facilitate  
star earthing of the cable clamp straps  
in the patch panels. The earth terminals  
are fully adjustable.

Current carrying capacity of rail approx. 200 A.

For network enclosure H: 1400 mm

Length of earth rail: 1145 mm