

Rittal – The System.

Faster – better – everywhere.



TS 8601.860 Earthquake base/plinth

State: 04.07.2026. (Source: rittal.com/hr-hr)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TS 8601.860 - Earthquake base/plinth for VX, TS

For stable attachment of the earthquake-resistant enclosure to the subsurface. External metric M10 thread for a stable connection to the subsurface from the outside.



Features

Model No.	TS 8601.860
Product description	For stable attachment of the earthquake-resistant enclosure to the subsurface. External metric M10 thread for a stable connection to the subsurface from the outside.
Material	Corner pieces: Sheet steel 5 mm Trim panels: Sheet steel 2 mm
Surface finish	Powder-coated
Colour	RAL 7022
Supply includes	Base/plinth, fully assembled 4 corner pieces 2 depth stays 2 trim panels front/rear Assembly parts
Note	Meets earthquake zone 4 to Telcordia GR-63-Core in conjunction with a comfort handle and an earthquake kit.
Dimensions	Height: 100 mm
To fit	Enclosure type: VX TS Width: = 800 mm Depth: = 600 mm
Packs of	1 pc(s).

Features

Net weight	15,06 kg
Gross weight	15,87 kg
PCF per pack (cradle-to-gate)	60.6 kg CO2 eq (Cat B)
Note on PCF category	Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared
Customs tariff number	94039910
ETIM 9	EC000721
ECLASS 8.0	27182003
Product description	TS Earthquake base/plinth for TS, H: 100 mm, for WD: 800x600 mm