Rittal – The System.

Faster – better – everywhere.





TS 8806.580 Baying systems TS 8

State: 24.11.2025. (Source: rittal.com/hr-hr)



TS 8806.580 - Baying systems TS 8 IP 66/NEMA 4

Baying systems TS 8, protection category IP 66, NEMA 4, sheet steel, spray-finished

Features

Model No.	TS 8806.580
Material	Enclosure frame: Sheet steel, 1.5 mm
	Roof: Sheet steel, 1.5 mm
	Door: Sheet steel, 2.0 mm
	Rear panel: Sheet steel, 1.5 mm
	Base: sheet steel, 1.5 mm
	Mounting plate: Sheet steel, 3.0 mm
Surface finish	Enclosure frame, door, roof and rear panel: Dipcoat-primed and
	powder-coated, textured paint
	Mounting plate: Zinc-plated
Colour	RAL 7035
Supply includes	Enclosure frame
	Door
	Door hinged on the right, may be swapped to the left
	Roof plate
	Base, solid
	Rear panel
	Mounting plate
	4 eyebolts
	Lock: 3 mm double-bit
	2 TS punched rails 18 x 38 mm
	2 support strips fitted in the enclosure depth
	Accessory kit for side panels for upgrading to IP 66
Dimensions	Width: 800 mm
	Height: 2,000 mm
	Depth: 600 mm
Dimensions mounting plate (W x H)	699 mm x 1,896 mm
Protection category to IEC 60 529	IP 66

© Rittal 2025

Features

Protection category NEMA	NEMA 1
	NEMA 4
	NEMA 12
Type rating to UL 50E	Type 1
	Type 4
	Type 12
IK Code	IK09
Basic material	Sheet steel
Packs of	1 pc(s).
Net weight	123.975
Gross weight	131.4
EAN	4028177597686
ETIM 9	EC000261
ECLASS 8.0	27180101

Approvals

Approvals	Bureau Veritas
	C-UL
	UL + C-UL (listed)
Certificates	Surface finish
Explanations	Manufacturer's declaration
	Declaration of conformity
	Declaration of conformity UK

© Rittal 2025 3