

# Rittal – The System.

Faster – better – everywhere.



# SV 9340.270 OM supports

State: 17.04.2026. (Source: [rittal.com/hr-hr](http://rittal.com/hr-hr))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



FRIEDHELM LOH GROUP

# SV 9340.270 - OM supports without contact system

For mounting of switchgear with external power supply.

## Features

|   |  |
|---|--|
| Model No.                                     | SV 9340.270  |
| Design  | without contact system                                 |
| Product description                           | For mounting of switchgear with external power supply. |
| Material                                      | Polyamide<br>Fire protection corresponding to UL 94-V0 |
| Colour  | Chassis: RAL 7035                                      |
| For bar systems with centre-to-centre spacing | 60 mm  |
| Support rail type                             | Support frame, 1 x TS 55D-V                            |
| Number of poles                               | 3-pole   |
| Support frame support                         | Yes  |
| Dimensions                                    | Width: 55 mm<br>Height: 272 mm                         |
| Support rails Qty/height                      | 1 / 10 mm  |
| To fit busbars                                | Height: 5, 10 mm                                       |
| Support frame (W x H)                         | 55 mm x 237 mm   |
| Approvals                                     | UL   |
| Packs of                                      | 1 pc(s).   |
| Net weight                                    | 0,25 kg  |
| Gross weight                                  | 0,258 kg   |
| Customs tariff number                         | 85369095   |
| ETIM 9  | EC001166   |
| ECLASS 8.0                                    | 27400607   |

# Features

---

Product description

SV OM Support, WH: 55x272 mm, support frame, support rail TS 55D-V, without contact system

# Approvals

---

Approvals

ABS  
DNV-GL  
Lloyds Register of Shipping  
UL + C-UL (listed)

Explanations

Declaration of conformity  
Declaration of conformity UK

# Tender text

OM support (without contact system)  
OM support without contact system (3-pole)  
for busbar thickness 5/10 mm and PLS 800/1600  
Technical specifications  
Construction width: 55 mm  
Length: 272 mm  
Support frame: 55 x 237 mm  
Support frame support: yes  
PinBlock: -  
Support rail: 1  
System:  
Rittal RiLine60