

Rittal – The System.

Faster – better – everywhere.



SV 9661.240

PE/PEN combination angle E-Cu

State: 23.05.2026. (Source: rittal.com/hr-hr)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SV 9661.240 - PE/PEN combination angle E-Cu for PE/PEN combinations

The PE/PEN combination, comprising busbars, combination angles and baying brackets, supports type-tested configurations as per IEC 61 439-1.

Features

| | |
|---|--|
| Model No. | SV 9661.240 |
| Product description | The PE/PEN combination, comprising busbars, combination angles and baying brackets, supports type-tested configurations as per IEC 61 439-1. |
| Benefits | Thanks to the pre-assembled combination angles, baying brackets and busbars customised to match the enclosure width, assembly is time-saving with cost reduction |
| Applications | Form 2-4 |
| Material | E-Cu |
| Supply includes | Assembly parts |
| Approved short-circuit current capability | I _{cs} 60 kA, 1 sec. |
| To fit busbars | Busbar E-Cu with integral punchings |
| OUT_CROSS_SECTION_COL_SM | 40 - 10 mm |
| To fit busbars | Width: 40, 80 Height: 10, 10 mm |
| Packs of | 4 pc(s). |
| Net weight | 2,2 kg |
| Gross weight | 2,356 kg |
| Copper weight (kg per piece) | 0,44 |
| Customs tariff number | 74198090 |
| ETIM 9 | EC000329 |
| ECLASS 8.0 | 27400605 |

Features

Product description

SV PE/PEN combination angle E-Cu, WH: 40x10 mm, L: 135 mm

Approvals

Explanations

Declaration of conformity

Declaration of conformity UK