

Rittal – The System.

Faster – better – everywhere.



VX 9680.206

Bayed enclosure system VX25

State: 06.05.2026. (Source: rittal.com/hr-hr)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



VX 9680.206 - Bayed enclosure system VX25 Fuse-switch-disconnector enclosure

Baying systems for the distribution of electrical power with NH slimline fuse-switch disconnectors (ABB or Jean Müller).



Features

| | |
|-----------------------------------|---|
| Model No. | VX 9680.206 |
| Material | Sheet steel, 1.5 mm |
| Surface finish | Enclosure frame: Dipcoat-primed Door, roof and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint Gland plates: Zinc-plated |
| Colour | RAL 7035 |
| Supply includes | Enclosure frame Door Roof plate Rear panel Gland plates Front trim panels Lock: 3 mm double-bit Compartment side panels Locating frame for disconnectors with fuses (brands ABB SlimLine/ Jean Müller SASIL) |
| Protection category to IEC 60 529 | Up to IP 2X (depending on the panels) |

Features

| | |
|-----------------------|---|
| Test specification | IEC 61 439-1/-2 IEC 61 641 |
| Dimensions | Width: 1,200 mm Height: 2,000 mm Depth: 600 mm |
| Packs of | 1 pc(s). |
| Net weight | 158,6 kg |
| Gross weight | 180,4 kg |
| Customs tariff number | 94032080 |
| ETIM 9 | EC000261 |
| ECLASS 8.0 | 27180101 |
| Product description | VX Fuse-switch disconnecter enclosure, WxHxD: 1200x2000x600 mm, sheet steel |

Approvals

| | |
|--------------|---------------------------|
| Certificates | Surface finish |
| Explanations | Declaration of conformity |