Rittal – The System.

Faster - better - everywhere.





SV 9686.030 **Busbar support**

State: 16.11.2025. (Source: rittal.com/hr-hr)



SV 9686.030 - Busbar support for busbar baying (roof section)

For baying busbar systems from enclosure to enclosure in the roof section.

Features

| Model No. | SV 9686.030 |
|-------------------------------------|--|
| Product description | For baying 3- or 4-pole flat copper busbar systems from enclosure to enclosure in the roof section. |
| Material | Duroplastic Fire protection corresponding to UL 94-V0 |
| Colour | Similar to RAL 9005 |
| Supply includes | Assembly parts |
| To fit busbars | 50 x 10 |
| Centre-to-centre spacing of busbars | 80 mm |
| Assembly instruction | For the installation of max. 4 busbars (sub-conductors) per phase Cage nut (M8) 4165.500 is required to attach the busbar support to the enclosure section |
| Packs of | 2 pc(s). |
| Net weight | 3 |
| Customs tariff number | 85469010 |
| EAN | 4028177935655 |
| ETIM 9 | EC001166 |
| ECLASS 8.0 | 27400607 |
| | |

Approvals

© Rittal 2025 2

Approvals

| Approvals | DNV-GL Lloyds Register of Shipping |
|--------------|---------------------------------------|
| Explanations | Declaration of conformity UK |

© Rittal 2025 3