Rittal - The System.

Faster – better – everywhere.





AX 2262.165 AX wall-mounted enclosure, 3-part


State: 7/12/2025 (Source: rittal.com/ie-en)



AX 2262.165 - AX wall-mounted enclosure, 3-part With Blue e+ outlet filter

The delivery concept behind the three-part AX wall-mounted enclosures reduces complexity and enhances flexibility. The AX/VX modular system makes these enclosures suitable for a range of applications. The three-part structure ensures easy access.







Features

21 U
Comfort handle for lock inserts and 2-point locking
2 Blue e+ outlet filters 3238.300 (supplied loose)
Centre part lock: 3 mm double-bit
Designer glazed door lock: Security lock 3524 E
Designer glazed door
installation
frame, and two 482.6 mm (19") mounting angles, front, static
Hinged part with 25 mm pitch pattern of holes in the front and rea
Wall section: Gland plate, solid, top and bottom
Glazed door: RAL 7035/7015 (slate grey)
Wall and hinged part: RAL 7035
Powder-coated
Viewing window: Single-pane safety glass, 3 mm
Wall and hinged part: Sheet steel, 1.5 mm
W.H I
Wall-mounted enclosures IT
AX 2262.165

© Rittal 2025 2

Features

Dimensions	Width: 600 mm
	Height: 1,012 mm
	Depth: 673 mm
Installation depth	620 mm
Clearances	Clearance width: 502 mm
	Clearance height: 951 mm
Depth hinged part	516 mm
Depth of wall section	135 mm
Number of locks	1
IK Code	IK08
Load capacity of hinged part (static)	750 N
Load capacity of wall section (static)	250 N
Basic material	Sheet steel
Lock	Lock version: Comfort handle and 2-point locking
	Lock insert: Security lock insert no. 3524 E
Protection category to IEC 60 529	IP 54 in conjunction with solid gland plate top and bottom
Customs tariff number	94032080
EAN	4028177994041
E-Number Sweden	E7238562

Approvals

Declaration of conformity

© Rittal 2025 3