

Faster – better – everywhere.





SK 3301.920 Overflow valve

State: 10/09/2025 (Source: rittal.com/ie-en)



POWER DISTRIBUTION >> CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

ENCLOSURES

SK 3301.920 - Overflow valve

Pressostat for use in the water cycle between the recooling system and the air/water heat exchanger. It prevents an increase in pump pressure in the recooling system against the closed magnetic value of the air/water heat exchanger outside of the cooling cycle.

Features

| Model No. | SK 3301.920 |
|-----------------------------------|--|
| Product description | Pressostat for use in the water cycle between the recooling system and the air/water heat exchanger. It prevents an increase in pump pressure in the recooling system against the closed magnetic valve of the air/water heat exchanger outside of the cooling cycle. |
| Material | Brass |
| Valve design | 1" bypass valve |
| OUT_PRESSURE_ADJUSTMENT_R ANGE | 2 - 12 bar |
| Packs of | 1 pc(s). |
| Net weight | 1.019 |
| Gross weight | 1.046 |
| Customs tariff number | 84818073 |
| EAN | 4028177448643 |
| ETIM 9 | EC000855 |
| ETIM 8 | EC000855 |
| ECLASS 8.0 | 27180704 |
| | |

Approvals

Certificates