

# Rittal – The System.

Faster – better – everywhere.



## AS 4055.473 Hole punch, sub-D

State: 15/06/2026 (Source: [rittal.com/ie-en](http://rittal.com/ie-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# AS 4055.473 - Hole punch, sub-D for sheet steel and stainless steel

For punching rectangular cut-outs for connectors

## Features

|  |   |
|--|---|
| Model No.  | AS 4055.473   |
| Product description                                    | For punching rectangular cut-outs for connectors. The hole punch is operated with a wrench or hydraulic punch.                    |
| Benefits   | With side ejector for the waste<br>No jamming of the die<br>Anti-twist axles for stamps and dies are used as tension bolts.       |
| Supply includes  | Female dies<br>Male dies<br>Tension bolts<br>Lock nut<br>Pressure nut with ball bearing<br>Adaptor for hydraulics<br>Plastic case |
| Machinable material                                    | Sheet steel<br>Stainless steel  |
| Maximum machinable material thickness, stainless steel | 1.25 mm   |
| Maximum machinable material thickness, sheet steel     | 1.75 mm   |
| ∅ punch  | 58.4 x 11.3 mm  |
| Packs of   | 1 pc(s).  |
| Net weight   | 0.695 kg  |
| Gross weight   | 0.873 kg  |
| Customs tariff number                                  | 82073010  |
| ECLASS 8.0   | 21049047  |

# Features

---

Product description

Hole punch, sub-D for sheet steel and stainless steel