Rittal – The System.

Faster - better - everywhere.





TX 5540.245 TX Colocation rack

State: 11/11/2025 (Source: rittal.com/ie-en)



TX 5540.245 - TX Colocation rack

The world of IT is changing, and the centralisation of IT in large data centres has become a long-term trend. The TX Colo, which is perfectly adapted to use in a large data centre, is our response. Thanks to its forward-thinking configuration, the TX Colo is ready for immediate use to suit your application!







Features

TX 5540.245 Standard
Standard
Gtandard
Sheet steel
Enclosure frame: Dipcoat-primed
Interior installation: Spray-finished
Doors and roof: Dipcoat-primed, powder-coated
Perforated Door, Sheet Steel
RAL 7035
Enclosure frame and roof: RAL 7035
Door: RAL 7035
Handle and hinges: RAL 9005

© Rittal 2025

Features

Supply includes	Enclosure frame with doors and roof plate Sheet steel front door, vented, 130° hinges Rear door made of sheet steel, divided, vented, 130° hinges Lock, front and rear: Comfort handle VX with numerical code Roof plate with cable entry across the full enclosure depth, left and right Divider panel, fitted to the left-hand side of the enclosure 150 mm cable tray, fitted to the rear, right-hand side of the enclosure 10 x captive nuts with screws (enclosed) Grounding accessories (supplied loose) Mounting angles, 482.6 mm (19") Air baffle plate Baying kit (supplied loose)
Material thickness - door	1.2 mm
Dimensions	Width: 600 mm Height: 2,450 mm Depth: 1,200 mm
Units	52 U
Distance between levels as delivered	745 mm
Distance between mounting levels min	115 mm
Distance between mounting levels max	341 mm
482.6 mm (19") attachment	600 mm-wide enclosure with mounting bracket screw-fastened to the frame at the top and bottom
Design	Standard
Roof design	Roof plate with cable entry across the full enclosure depth, left and right
Design doors	Vented doors
Rear door design	Sheet steel door, vented two-piece Vented surface area approx. 78 % perforated

© Rittal 2025 3

Features

Front door design	Sheet steel door, vented
	Aluminium/sheet steel door, vented
	one-piece
	Vented surface area approx. 78 % perforated
Base design	Open
Mounting angles position	482.6 mm (19") level, front and rear
Load capacity	15,000 N
Note	Depending on how and where it is sited, the door opening angle may vary for selected applications
Packs of	1 pc(s).
Net weight	125
Gross weight	132
Customs tariff number	94032080
EAN	4028177971639
ETIM 9	EC002499
ETIM 8	EC002499
ECLASS 8.0	27180207

Approvals

Explanations	Declaration of conformity
	Declaration of conformity UK

© Rittal 2025