

Rittal – The System.

Faster – better – everywhere.



SV 9341.050 Busbar support PLS

State: 21/05/2026 (Source: rittal.com/ie-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SV 9341.050 - Busbar support PLS

For PLS special busbars 800 A/1600 A, 3-pole and 4-pole, suitable for top-mounting.

Features

| | |
|------------------------------|--|
| Model No. | SV 9341.050 |
| Material | Polyamide Fire protection corresponding to UL 94-V0 |
| Colour | RAL 7035 |
| Rated operating voltage | 1000 V, 3~ 1500 V (DC) |
| Electrical ratings UL (SCCR) | 14 kA - 600 V, support spacing 500 mm, PLS 800 busbars 22 kA - 600 V, support spacing 200 mm, PLS 800 busbars 50 kA - 600 V, support spacing 250 mm, PLS 800 busbars, circuit breaker max. 600 A, DIVQ/7 50 kA - 600 V, support spacing 250 mm, PLS 800 busbars, Fuse Class L max. 800 A, JDDZ/7 65 kA - 480 V, support spacing 150 mm, PLS 800 busbars, circuit breaker max. 600 A, DIVQ/7 65 kA - 600 V, support spacing 150 mm, PLS 800 busbars, Fuse Class max. 600 A, JDDZ/7 |
| Note on Model No. | The use of a base tray is required for UL applications UL approval only applies in conjunction with AC application |
| Top-mounting | Yes |
| Number of poles | 3-pole |
| To fit busbars | PLS 800 |
| To fit Model No. | 3516.000 3527.000 3528.000 3528.010 3529.000 |
| Internal attachment | Yes |

Features

| | |
|-------------------------------------|--|
| Centre-to-centre spacing of busbars | 60 mm |
| Approvals | UL |
| Packs of | 4 pc(s). |
| Net weight | 0.32 kg |
| Gross weight | 0.368 kg |
| Customs tariff number | 85469010 |
| ETIM 9 | EC001166 |
| ECLASS 8.0 | 27400607 |
| Product description | SV Busbar support, PLS 800, 3-pole, 60 mm bar centre distance, UL design |

Approvals

| | |
|--------------|---|
| Approvals | ABS Lloyds Register UL + C-UL (listed) |
| Explanations | Declaration of conformity Declaration of conformity UK |

Tender text

PLS 800 UL busbar support

PLS 800 UL busbar support

3-pole

Technical specifications

Bar centre distance: 60 mm

Busbars: PLS 800 special busbar

Construction width: 20 mm

Length: 190 mm

Note

The use of the base tray is compulsory for UL applications.