Rittal - The System.

Faster – better – everywhere.





SV 9344.310 NH fuse-switch disconnector

State: 17/11/2025 (Source: rittal.com/ie-en)



SV 9344.310 - NH fuse-switch disconnector

Features

Model No.	SV 9344.310
Material	Polyamide Fire protection corresponding to UL 94 Contact tracks: Electrolytic copper, silver-plated
Colour	Chassis: RAL 7035 Cover: RAL 7035/7001
Clamping area for laminated copper bars	Clamping area width: 50 mm Clamping area height: 10 mm
for mounting plate assembly	Yes
Cable outlet	Top/bottom
Type of electrical connection	Screw M10
Rated operating current max.	630 A
Rated operating voltage	690 V, 3~
For NH size	3
Note	The technical data may vary for UR applications. Applications to UR only in conjunction with "Special Purpose Fuses".
Test specification	IEC/DIN EN 60 947-3 DIN EN 60 269-2 (fuse inserts)
Dimensions	Width: 250 mm Height: 298 mm
Connection of round conductors	10 - 300 mm²
Number of poles	3-pole
Cross section round conductor	10 - 300 mm²
Packs of	1 pc(s).
Net weight	3.6
Gross weight	3.8

© Rittal 2025

Features

Copper weight (kg per piece)	1.06
Customs tariff number	85369095
EAN	4028177540736
ETIM 9	EC000249
ECLASS 8.0	27371401

Approvals

Approvals	C-UR
	CQC-CCC
	UR + C-UR (recognized)
Explanations	Declaration of conformity
	Declaration of conformity UK

© Rittal 2025 3