

Rittal – The System.

Faster – better – everywhere.



SK 3213.360

Air diverter

State: 19/3/2026 (Source: rittal.com/in-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE


SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SK 3213.360 - Air diverter

Targeted routing of the cold air flow to avoid hot spots in the enclosure. Particularly well-suited for densely-packed electrical components in the enclosure.



Features

Model No.	SK 3213.360
Product description	For use with wall-mounted cooling units, for targeted routing of cold air in a downward direction. Particularly well-suited for densely-packed electrical components in the lower section of the enclosure.
Benefits	Individual modification of air outlet direction Simple, tool-free assembly Quickly retrofitted (no drilling required) Minimum installation depth
Material	ABS Fire protection corresponding to UL 94-V0
Colour	RAL 7035
To fit	Wall-mounted cooling unit Blue e+
Note on Model No.	Not suitable for wall-mounted cooling unit Blue e+ Outdoor
To fit Model No.	3184.xx0 3186.93x 3186.630 3187.93x 3187.630
Dimensions	Width: 330 mm Height: 330 mm Depth: 30 mm
Packs of	1 pc(s).

Features

Net weight	0.6 kg
Gross weight	0.64 kg
Customs tariff number	39269097
ETIM 9	EC011604
ETIM 8	EC011604
ECLASS 8.0	22410601
Product description	SK Air diverter, for SK 3184.xx0/3186.93x/.630/3187.93x/.630
