

Faster – better – everywhere.





# SK 3240.400 Blue e+ outlet filter

POWER DISTRIBUTION SCIENATE CONTROL

State: 24/8/2025 (Source: rittal.com/in-en)



IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

ENCLOSURES

## SK 3240.400 - Blue e+ outlet filter EMC

The outlet filter is used in conjunction with the corresponding fan-and-filter unit to dissipate heat loss from enclosures, ventilate the enclosure and protect temperature-sensitive components. This is achieved through the direct infeed of ambient air, the temperature of which must be lower than the permissible internal temperature of the enclosure.



#### Features

Model No.	SK 3240.400
	SK 3240.400
Design	wall-mounted
	EMC
Benefits	Easy filter changes, thanks to a new opening mechanism on the
	louvred grille
	Faster installation on the enclosure with optimised detent hooks
	Tool-free assembly
Colour	RAL 7035
Supply includes	Outlet filter
	EMC filter mat
Mounting cut-out	Cut-out width: 224 mm
	Cut-out height: 224 mm
To fit Model No.	SK 3240.8xx/3241.8xx
Dimensions	Width: 255 mm
	Height: 255 mm
	Depth: 45.2 mm

## Features

Protection category NEMA	Type 12 with chopped-fibre filter Type 3, 3R, 4, 4X with chopped-fibre filter and hose-proof hood
IP protection category to IEC 60 529	IP 54 with chopped-fibre filter IP 56 with chopped-fibre filter and hose-proof hood
Packs of	1 pc(s).
Net weight	0.4
Gross weight	0.661
Customs tariff number	39269097
EAN	4028177998346
ETIM 9	EC002513
ETIM 8	EC002513
ECLASS 8.0	27180706

# Approvals

Approvals

UL + C-UL - FTTA UR + C-UR (recognized)