

# Rittal – The System.

Faster – better – everywhere.



## SK 3314.025 Active module

State: 3/6/2026 (Source: [rittal.com/in-en](http://rittal.com/in-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE


SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SK 3314.025 - Active module for LCP Rear Door CW

Active module to support air routing via the passive module. Easily retro-fitted by locating into the service door. Control may be based on the ambient air temperature or (optionally) differential pressure. I/O board, sensors, DC fan and essential interfaces and protocols are pre-integrated.



## Features

Model No.	SK 3314.025
Design	Room cooling CW
Benefits	Volumetric airflow is boosted via the heat exchanger to increase the cooling output
Applications	In conjunction with the passive and active modules of the LCP Rear Door CW portfolio
Function principle	Regulation of brushless DC fans using the ambient air temperature or optionally via differential pressure to ensure the software's condensate prevention function.
Material	Sheet steel Copper Plastic
Surface finish	RAL 9005, finely textured matt RAL 9005, finely textured matt
Note	A water module is essential for condensation prevention by the software and display of the cooling output.
Dimensions	Width: 372 mm Height: 2,066 mm Depth: 123 mm

# Features

---

Rated operating voltage	100 V - 240 V, 1~, 50 Hz/60 Hz
Rated power input	0.47 kW
Rated current (max.)	4.8 A
Operating temperature range	10 °C...50 °C
Sound power level	At 50% speed: 77 dB(A) At 100% speed: 87 dB(A)
Sound pressure level at a distance of 1 m	At 50% speed: 71 dB(A) At 100% speed: 78 dB(A)
Packs of	1 pc(s).
Net weight	26 kg
Gross weight	27 kg
Customs tariff number	84145915
Product description	SK active module for LCP RD CW, for height = 2200 mm, RAL 9005, finely textured matt, including 16 pc(s) brushless direct current (BLDC) fans, I/O board

# Approvals

---

Approvals	UR + C-UR (recognized)
Explanations	Declaration of conformity