

Rittal – The System.

Faster – better – everywhere.



SV 3583.000 Busbars E-Cu

State: 6/6/2026 (Source: rittal.com/in-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SV 3583.000 - Busbars E-Cu

Length: 2400 mm/bar.



Features

| | |
|------------------------------|--|
| Model No. | SV 3583.000 |
| Material | E-Cu F30 |
| Note | May be cut individually to required length |
| Standards | DIN EN 13 601 |
| Cross-section | 25 mm x 5 mm |
| Dimensions | Length: 2,400 mm |
| Packs of | 6 pc(s). |
| Net weight | 15.9 kg |
| Gross weight | 16.16 kg |
| Copper weight (kg per piece) | 2.68 |
| Customs tariff number | 74071000 |
| ETIM 9 | EC001522 |
| ETIM 8 | EC001522 |
| ECLASS 8.0 | 27370303 |
| Product description | SV Busbar E-Cu, WH: 25x5 mm, L: 2400 mm |

Approvals

| | |
|--------------|---|
| Approvals | UL + C-UL (listed) |
| Explanations | Declaration of conformity Declaration of conformity UK |

Tender text

Busbar made from E-Cu
Busbars E-Cu to DIN 13601
Technical specifications
Length: 2400 mm
Dimension: 25 x 5mm
Cross section: 124 qmm
Weight: 1.11 Kg/m
Electrical parameters
IEC: to 384 A
UL 508: 290 A
System:
Rittal RiLine60