

Rittal – The System.

Faster – better – everywhere.



CP 6372.561 Comfort Panel

State: 21/6/2025 (Source: rittal.com/in-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



CP 6372.561 - Comfort Panel

Aluminium enclosure, high thermal conductivity for optimum passive heat dissipation. Low weight coupled with high stability. Protection category IP 65 to IEC 60 529.



Features

| | |
|--------------------|--|
| Model No. | CP 6372.561 |
| Design | Support arm connection, rectangular 120 x 65 mm |
| Benefits | Aluminium enclosure, high thermal conductivity for optimum passive heat dissipation. Low weight coupled with high stability Compatible with all Rittal stand and support arm systems |
| Material | Enclosure: Extruded aluminium section Corner pieces: Die-cast zinc Corner protectors: Plastic |
| General colour | Natural anodised |
| Colour | Enclosure: Natural anodised Corner pieces: RAL 7035 Corner protectors: similar to RAL 7024 |
| Supply includes | Enclosure with cut-out for support arm connection 3 mm double-bit lock insert may be exchanged for 41 mm lock inserts, plastic handles and T handles, type C Seals and assembly parts for front panels Hinged rear panel, hinging on the longest side |
| Installation depth | 74 mm |

Features

| | |
|-------------------------------------|--|
| IP protection category to IEC 60529 | IP 65 |
| Protection category NEMA | NEMA 12 |
| To fit front panel width | 520 mm |
| To fit front panel height | 600 mm |
| Design | Servicing access from the rear |
| Note | The support arm connection may be swapped over by rotating the enclosure |
| Basic material | Aluminium |
| Lock | Lock version: Screw lock |
| Packs of | 1 pc(s). |
| Net weight | 10.3 |
| Gross weight | 13.2 |
| EAN | 4028177663121 |
| ETIM 9 | EC002504 |
| ECLASS 8.0 | 27180505 |

Approvals

| | |
|--------------|---|
| Approvals | UL + C-UL (listed) |
| Explanations | Declaration of conformity Declaration of conformity UK |