


# Rittal – The System.

Faster – better – everywhere.



## CP 6380.610 Optipanel

State: 11/9/2025 (Source: [rittal.com/in-en](http://rittal.com/in-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# CP 6380.610 - Optipanel

Aluminium enclosure, high thermal conductivity for optimum passive heat dissipation. For smaller panels and control solutions. Super-slimline design, needs hardly more space than the installed equipment itself.



## Features

|                    |  |
|--------------------|--|
| Model No.          | CP 6380.610  |
| Design             | Support arm connection Ø 130 mm  |
| Benefits           | Aluminium enclosure, high thermal conductivity for optimum passive heat dissipation.<br>Low weight coupled with high stability<br>Compatible with all Rittal stand and support arm systems |
| Material           | Enclosure: Extruded aluminium section<br>Corner pieces: Die-cast zinc<br>Corner protectors: Plastic  |
| General colour     | Natural anodised   |
| Colour             | Enclosure: Natural anodised<br>Corner pieces: RAL 7035<br>Corner protectors: similar to RAL 7024   |
| Supply includes    | Enclosure with hinged rear panel<br>Seals<br>Seals and assembly parts for front panels   |
| Installation depth | 150 mm   |

# Features

|                                     |   |
|-------------------------------------|---|
| IP protection category to IEC 60529 | IP 65   |
| To fit front panel width            | 520 mm  |
| To fit front panel height           | 600 mm  |
| Design                              | Servicing access from the rear  |
| Note                                | The support arm connection may be swapped over by rotating the enclosure<br>3 mm double-bit lock insert may be exchanged for 41 mm lock inserts, plastic handles and T handles, type C<br>Hinging of the rear panel on the longest enclosure side |
| Basic material                      | Aluminium   |
| Lock                                | Lock version: Cam<br>Number of locks: 2<br>Lock insert: 3 mm double-bit   |
| Packs of                            | 1 pc(s).  |
| Net weight                          | 11.542  |
| Gross weight                        | 12.149  |
| Customs tariff number               | 94032080  |
| EAN                                 | 4028177663206   |
| ETIM 9                              | EC002504  |
| ECLASS 8.0                          | 27180505  |

# Approvals

|              |   |
|--------------|---|
| Approvals    | UL + C-UL (listed)  |
| Explanations | Declaration of conformity<br>Declaration of conformity UK |