

# Rittal – The System.

Faster – better – everywhere.



## DK 7856.204

## PSM socket modules

State: 20/6/2025 (Source: [rittal.com/in-en](https://www.rittal.com/in-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# DK 7856.204 - PSM socket modules

The various modules may be inserted into the support rail in any combination.

## Features

Model No.	DK 7856.204
Design	switchable with aggregate current measurement per module
Product description	The modular system facilitates basic configuration of the racks, thanks to a vertical support rail with single-/3-phase infeed. The various socket modules to supply the active components may be snap-fitted into the support rail. The various modules, earthing pins, IEC320 etc. may be inserted into the support rail in any combination. This is easily achieved, even by non-electricians, thanks to the shock hazard protected plug & play system.
Material	Section: Aluminium, anodised Socket inserts: Plastic (PA6 GF 30 V1)
Length	250 mm
Thermal overcurrent protection	per socket module
Rated operating voltage	110 V – 230 V AC, 50/60 Hz
Rated current (max.)	16 A
Required number of module slots	2
Dimensions	Length: 250 mm
Operating temperature range	5 °C...45 °C
Ambient humidity (non-condensing)	5...95 %
Sockets	4 x IEC 320 socket C19 2 x IEC 320 socket C13
Packs of	1 pc(s).
Net weight	1.019
Gross weight	1.087
Customs tariff number	85369001

## Features

EAN	4028177552890
ETIM 9	EC000330
ECLASS 8.0	27142604

## Approvals

Explanations	Declaration of conformity
--------------	---------------------------

## Tender text

PSM 6-way active plug in module, 2xC13+4xC19

The Power System Module socket strip has 6 power outlets with 2 x IEC320 C13 and 4 x IEC320 C19. The functions include current display, circuit display, automatic selective switching via HTTP and SNMP via CMC-TC in the network: individual switching of the 6 power outputs, current limit monitoring without time delayed switching of the individual power outputs. A separate power unit (7201.210) and the relevant connection cable (7856.025 -.026) are required for stand-alone operation without a CMC-TC.

Packs of 1