

TS 8612.080 TS punched section with mounting flange, 17 x 73 mm

IT INFRASTRUCTURE SOFTWARE & SERVICES

State: 8/9/2025 (Source: rittal.com/in-en)

RITTAL

R DISTRIBUTION CLIMATE CONTROL

FRIEDHELM LOH GROUP

ENCLOSURES

TS 8612.080 - TS punched section with mounting flange, 17 x 73 mm

For universal skeleton structures or partial assembly. Simply locate into the punchings and secure.



Features

TS 8612.080
For the inner mounting level and for mounting on doors
For universal skeleton structures or partial assembly. Simply locate into the punchings and secure.
Sheet steel
Zinc-plated
Assembly screws
790 mm
900 mm
On the vertical TS, VX SE enclosure section: On the inner mounting level, height-offset all-round For SE, may additionally be mounted on the top horizontal section ir the depth In the tubular door frame for TS, SE and PC In TP via rail for interior installation: In the width, for inner mounting level
As a mounting kit for component shelves in TS, VX SE, simply locate and secure The rail for internal mounting is required when installing in TP

Features

To fit	Enclosure type: VX SE
	TP
	PC
	IW
	TX CableNet
	To fit width/depth: 800 mm
Packs of	4 pc(s).
Net weight	3.384
Gross weight	3.54
PCF per pack (cradle-to-gate)	13.7 kg CO2 eq (Cat B)
Note on PCF category	Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared
Customs tariff number	73269098
EAN	4028177212107
ETIM 9	EC002625
ECLASS 8.0	27189234