


# Rittal – The System.

Faster – better – everywhere.



## SV 9635.300

## Component adaptor

State: 23/1/2026 (Source: [rittal.com/in-en](http://rittal.com/in-en))



# SV 9635.300 - Component adaptor 3-pole

For assembly of switchgear and protective gear.

## Features

Model No.	SV 9635.300
Design	With integral fuse holder
Function principle	For mechanical attachment and direct contacting of electrical equipment on the board
Material	Polyamide Fire protection corresponding to UL 94
Colour	RAL 7035
Note	The technical data may vary for UL applications
Rated current max.	16 A
Rated operating voltage	690 V (AC) 600 V (DC)
Number of poles	3-pole
For fuse type (class)	CC
Electrical ratings UL	Rated operating voltage (max.) UL: 600 V AC
Connection cables (AWG)	AWG 14
Length of connection cable	125 mm
Support rails Qty/height	1 / 10 mm
Support rail type	static
Dimensions	Width: 22.5 mm Height: 160 mm Depth: 80 mm
Packs of	1 pc(s).
Net weight	0.124
Gross weight	0.134

## Features

---

Copper weight (kg per piece) 0.02

---

Customs tariff number 85369095

---

EAN 4028177817388

---

ETIM 9 EC001531

---

ECLASS 8.0 27370304

## Approvals

---

Approvals UL + C-UL (listed)

---

Explanations Declaration of conformity  
Declaration of conformity UK