

# Rittal – The System.

Faster – better – everywhere.



## DK 7010.160

## センサー

State: 2026/03/29 (Source: [rittal.com/jp-ja](http://rittal.com/jp-ja))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# DK 7010.160 - センサー CMC III、PDU、LCP、IoT インターフェース用

The access monitoring sensor uses infrared light to monitor whether the door of an enclosure is open or closed. An integrated vibration sensor emits an alarm if vandalism is detected.

## Features

品番	DK 7010.160
仕様	アクセス監視センサー
メリット	プラグアンドプレイによる早い接続と自動認識 給電は、CANバスインターフェース経由で行われます。
用途	IT、工業と産業、建築技術におけるエンクロージャーの監視。 IT環境にあるエンクロージャー、ルームおよびコンテナを監視します。
機能方法	センサーには、赤外線発信器および受信機が内蔵されています。 アクセス監視センサーは、赤外線を使って、エンクロージャーのドアが開いているか閉じているかを監視します アクセス監視センサーは、3軸方向(x y z)に働く引力(g力)を監視します センサーは、エンクロージャー内でドア向きに取り付けられ、光はドアに付いている反射テープで反射されます。 センサーは、エンクロージャーフレームに取り付けられ、エンクロージャーに影響を与える振動はセンサーへと伝わって行きます。 CMC III プロセッシングユニット、PDU、またはIoT インターフェース経由で設定可能です。
材質	プラスチック

# Features

表面	フロント側：光沢仕上げ エンクロージャー：テクスチャー
塗装色	RAL 9005
同梱品	センサー マウンティングプレート 取り付け部品を含む
CANバスへの接続	直接
インターフェース	2 x RJ45 CANバス ポート
寸法：	幅: 110 mm 高さ: 30 mm 奥行: 40 mm
動作温度範囲	0 °C...55 °C
湿度(結露無きこと)	5...95 %
1パック	1 個
純質量	0.063 kg
総質量	0.163 kg
関税率番号	85319000
ETIM 9	EC002627
製品説明	DK アクセス監視センサー、CAN バスインターフェース経由で接続、幅x高さx奥行 110x30x40 mm、RAL 9005

# Approvals

Approvals	UL + C-UL (listed)
-----------	--------------------

# Approvals

---

Explanations

CE適合宣言書