

Rittal – The System.

Faster – better – everywhere.



AS 4051.222

WT vibratory bowl feeder

Состояние: 12.05.2026 (Источник: rittal.com/kz-ru)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AS 4051.222 - WT vibratory bowl feeder

WT 29 vibratory bowl feeder for guiding loose wire end ferrules with plastic collars for cross-sections 1.5 and 2.5 mm² into the Wire Terminal WT C fully automated wire processing machine.



Функции

Арт. №	AS 4051.222
Исполнение	WT 29 vibratory bowl feeder
Преимущества	Process reliability with the infeed of wire end ferrules Simple, fast changeover of consumable materials
Технические характеристики	Suitable for wire end ferrule lengths from 8 - 18 mm
Комплект поставки	WT 29 vibratory bowl feeder
Области применения	For loose wire end ferrules with cross-section 1.5 mm ² and 2.5 mm ²
Указание	The vibratory bowl feeders and the separation of single wire end ferrules are designed for the dimensional tolerances of Rittal wire end ferrules to DIN 46228-4:2019-02. If the wire end ferrules used exceed the defined dimension tolerances, it may be necessary to design/test a new bowl feeder and to adapt the wire end ferrule separation.
Стандарты	AEH DIN 46228
Подходит для арт. №	4051.205 4051.210
Упаковка	1 шт.
Вес нетто	0,4 kg
Gross weight	0,7 kg
Код ТНВЭД	84799070