Rittal – The System.

Faster – better – everywhere.

RX 9360.230

RiLineX connection adaptor

Состояние: 22.09.2025 (Источник: rittal.com/kz-ru)

RX 9360.230 - RiLineX connection adaptor

RiLineX connection adaptor for 60 mm busbar systems. The device has a screw fastening, and is suitable for bar widths of between 5 and 10 mm.

Функции

Арт. №	RX 9360.230
Преимущества	Mounting on the busbar system and cable connection with just one screw
Материал	Полиамид (PA 6) Негорючесть согласно UL 94
Цвет	RAL 9005
Rated current of round conductor	630 A
Rated current of round conductor (UL)	600 A
Rated current of laminated copper bar	790 A
Rated current of laminated copper bar (UL)	760 A
Electrical ratings UL (SCCR)	27.5 kA - 600 V, RMS 100 kA - 600 V, circuit breaker max. 400 A, DIVQ/7 100 kA - 600 V, Fuse Class L max. 1200 A, JDDZ/7
Отвод проводов	сверху/снизу
Для шинных систем с межцентровым расстоянием	60 mm
Количество полюсов	3-пол.

Функции

Подходит для шинной системы	RiLineX RiLine60
Размер	Ширина: 128 мм Высота: 240 мм Глубина: 105 мм
Подключение проводов	95 - 240 мм²
Подключение проводов, тонкопроволочных с наконечником	95 - 240 мм²
Connection of round conductors, fine wire with AWG wire end ferrule	AWG 3/0 - AWG 450
Подключение проводов, многопроволочных	95 - 240 мм²
Connection of round conductors, multi-wire mm²	AWG 3/0 - AWG 450
Connection of sector-shaped conductors, single-wire	120 - 240 мм²
Connection of sector-shaped conductors, single-wire AWG	AWG 4/0 - AWG 450 kcmil
Connection of sector-shaped conductors, multi-wire	95 - 240 мм²
Connection of sector-shaped conductors, multi-wire AWG	AWG 3/0 - AWG 450 kcmil
Connection sector conductor (max.)	240 мм²
Клемма для гибких медных шин (Ш x В)	24 x 20 мм
Rated voltage	1 000 V AC 1 500 V DC 600 V AC (UL) 600 V DC (UL)
Категория перенапряжения	4
Степень загрязнения	3

Функции

Стандарты	IEC/EN 61439-1 UL 508
Номинальное импульсное напряжение Uimp	12 кВ
Rated insulation voltage	1 000 В
Power dissipation (max.)	20 Вт
Степень защиты IP согл. МЭК 60 529	IP 2XB
Operation humidity max	90 %
Диапазон рабочих температур	-5 °C...55 °C
Диапазон температур хранения	-25 °C...75 °C
Влажность воздуха (без конденсата)	10...90 %
Упаковка	1 шт.
Вес нетто	1.5
Gross weight	1.62
Код ТНВЭД	85369010
EAN	4028177997233
ETIM 9	EC001531

Одобрения

Одобрения	UL + C-UL (listed)
Объяснения	Декларация о соответствии