

Faster – better – everywhere.





IT INFRASTRUCTURE SOFTWARE & SERVICES

KX 1568.000 Terminal box KX

POWER DISTRIBUTION

CLIMATE CONTROL

State: 2025.7.24 (Source: rittal.com/lt-en)




FRIEDHELM LOH GROUP

ENCLOSURES

KX 1568.000 - Terminal box KX Stainless steel

The stainless steel terminal box KX delivers maximum data quality and consistency of engineering while ensuring flexibility and reliability across a wide range of applications.



Features

Model No.	KX 1568.000
Product description	The stainless steel terminal box KX delivers maximum data quality and consistency of engineering while ensuring flexibility and reliability across a wide range of applications.
Material	Enclosure: Stainless steel 1.4301 (AISI 304) Cover: Stainless steel 1.4301 (AISI 304), all-round foamed-in PU sea
Surface finish	Enclosure and cover: Brushed, grain 180
Supply includes	Enclosure with cover Quick-release fastener including plastic bushes
Protection category NEMA	NEMA 1 NEMA 3R NEMA 3RX NEMA 4 NEMA 4X NEMA 12
Protection category to IEC 60 529	IP 66

Features

Type rating to UL 50E	Туре 1
	Type 3R
	Type 3RX
	Туре 4
	Type 4X
	Туре 12
Dimensions	Width: 400 mm
	Height: 200 mm
	Depth: 120 mm
Material thickness - cover	1.25 mm
Material thickness - enclosure	1.25 mm
Lock	Number of locks: 4
Basic material	Stainless steel 1.4301 (AISI 304)
Packs of	1 pc(s).
Net weight	3.62
Gross weight	3.66
Customs tariff number	84879090
EAN	4028177919082
E-Number Sweden	E3465234
ETIM 9	EC000261
ETIM 8	EC000261
ECLASS 8.0	27180101

Approvals

Approvals	Bureau Veritas
	DNV-GL
	Lloyds Register of Shipping
	UL + C-UL (listed)
	UL + C-UL (listed)

Approvals

Explanations

Declaration of conformity Declaration of conformity UK

Tender text

Enclosure (terminal box, stainless steel)

Enclosure with cover:

Stable stainless steel design,

body folded from a single piece and welded,

with protection channel all-round cover opening,

Solid rear panel with knockouts,

cover with foamed-in PU seal,

with PE conductor connection in the enclosure,

earthing in the cover via bolt,

for quick and easy earthing,

with quick-release fastener.

QR code:

QR code printed on body, cover and rating plate

for clear identification and easy retrieval of relevant

product information and documentation,

and for clear traceability of the individual parts.

Accessories: Cover hinge,

mounting plate, top hat rail, wall mounting bracket,

mounting claw for second mounting level. Material:

Enclosure, cover: Stainless steel 1.4301 (AISI 304)

Surface finish: Brushed, grain size 180

Protection category to IEC 60 529: IP 66

Protection category to UL 508A: Type 4X

Dimensions (W x H x D): 400x200x120 mm