

Rittal – The System.

Faster – better – everywhere.



SK 3301.920 Overflow valve

State: 2026.7.2 (Source: rittal.com/lt-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SK 3301.920 - Overflow valve

Pressostat for use in the water cycle between the recooling system and the air/water heat exchanger. It prevents an increase in pump pressure in the recooling system against the closed magnetic valve of the air/water heat exchanger outside of the cooling cycle.

Features

Model No.	SK 3301.920
Product description	Pressostat for use in the water cycle between the recooling system and the air/water heat exchanger. It prevents an increase in pump pressure in the recooling system against the closed magnetic valve of the air/water heat exchanger outside of the cooling cycle.
Material	Brass
Valve design	1" bypass valve
OUT_PRESSURE_ADJUSTMENT_RANGE	2 - 12 bar
Packs of	1 pc(s).
Net weight	1.019 kg
Gross weight	1.046 kg
Customs tariff number	84818059
ETIM 9	EC000855
ETIM 8	EC000855
ECLASS 8.0	27180704
Product description	SK Bypass valve 1", for use with recooling systems and air/water heat exchangers, 2-12 bar, presetting 3 bar