

Rittal – The System.

Faster – better – everywhere.



DK 7050.100 Support unit, 3 U

State: 2026.7.7 (Source: rittal.com/lt-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



DK 7050.100 - Support unit, 3 U for LSA-Plus strips, max. 150 paired wires

For LSA-Plus strips, max. 150 paired wires, to accommodate a maximum of 15 LSA-Plusstrips (each with 10 paired wires). 3 x 5 LSA-Plus connection strips 2/10, series 2, horizontally.

Features

Model No.	DK 7050.100
Product description	To accommodate a maximum of 15 LSA-Plus strips (each with 10 paired wires). 3 x 5 LSA-Plus connection strips 2/10, series 2, may be installed horizontally. Strip length 124 mm, height pitch pattern 22.5 mm. The support unit may be integrated in all 482.6 mm (19") mounting levels. The mounting level is recessed 75 mm behind the 482.6 mm (19") flanges. Integral shunting rings enable tidy routing and distribution of the telecommunication cables.
Material	Stainless steel
Supply includes	Support unit, 8 shunting rings
Packs of	1 pc(s).
Net weight	0.68 kg
Gross weight	0.8 kg
Customs tariff number	94039910
ETIM 9	EC002620
ECLASS 8.0	27189261
Product description	DK Support unit for LSA strips, 3 U

Tender text

482.6 mm (19") support unit, 3 U to accommodate LSA-Plus strips

To accommodate a maximum of 15 LSA-Plus strips (each with 10 paired wires). 3 x 5 LSA-Plus strips may be installed horizontally in a pitch pattern distance of 22.5 mm in the support unit of stainless steel. The mounting level is recessed 100 mm behind the 482.6 mm flanges.

The support unit can be integrated into all 482.6 mm (19") mounting angles. Shunting rings enable tidy routing and distribution of the telecommunication cables.

Material: stainless steel