

**Rittal – The System.**

Faster – better – everywhere.



# SV 9344.250 NH fuse-switch disconnecter

State: 2026.4.13 (Source: [rittal.com/lt-en](http://rittal.com/lt-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SV 9344.250 - NH fuse-switch disconnecter with electromechanical fuse monitoring

## Features

|   |   |
|---|---|
| Model No.                               | SV 9344.250   |
| Design                                  | For mounting plate assembly   |
| Material                                | Polyamide<br>Fire protection corresponding to UL 94<br>Contact tracks: Electrolytic copper, silver-plated |
| Colour                                  | Chassis: RAL 7035<br>Cover: RAL 7035/7001   |
| Clamping area for laminated copper bars | Clamping area width: 50 mm<br>Clamping area height: 10 mm   |
| for mounting plate assembly             | Yes   |
| Cable outlet                            | Top/bottom  |
| Type of electrical connection           | Screw M10   |
| Rated operating current max.            | 400 A   |
| Rated operating voltage                 | 690 V, 3~   |
| For NH size                             | 2   |
| Test specification                      | IEC/DIN EN 60 947-3<br>DIN EN 60 269-2 (fuse inserts)   |
| Dimensions                              | Width: 210 mm<br>Height: 298 mm   |
| Connection of round conductors          | 10 - 240 mm <sup>2</sup>  |
| Number of poles                         | 3-pole  |
| Round conductor cross-section           | 10 - 240 mm <sup>2</sup>  |
| Packs of                                | 1 pc(s).  |
| Net weight                              | 3.4 kg  |

# Features

---

|                              |  |
|------------------------------|--|
| Gross weight                 | 3.481 kg   |
| Copper weight (kg per piece) | 1  |
| Customs tariff number        | 85369095   |
| ETIM 9                       | EC000249   |
| ECLASS 8.0                   | 27371401   |
| Product description          | SV NH fuse-switch disconnecter, size 2, 400 A, 690 V, 3-pole, screw M10, with electromechanical fuse monitoring, for mounting plate assembly |

# Approvals

---

|              |   |
|--------------|---|
| Approvals    | CQC-CCC   |
| Explanations | Declaration of conformity<br>Declaration of conformity UK |