


Rittal – The System.

Faster – better – everywhere.



VX 9680.426

Bayed enclosure system VX25

State: 2026.2.4 (Source: ittal.com/lt-en)



FRIEDHELM LOH GROUP

VX 9680.426 - Bayed enclosure system VX25 Modular enclosure

Baying systems VX, for installation with partial doors and internal separation in a modular design.

Features

Model No.	VX 9680.426
Material	Sheet steel, 1.5 mm
Surface finish	Enclosure frame: Dipcoat-primed Rear panel: Dipcoat-primed, powder-coated on the outside, textured paint Gland plates: Zinc-plated
Colour	RAL 7035
Supply includes	Enclosure frame Rear panel Gland plates
Protection category to IEC 60 529	Up to IP 54, depending on the panels
Test specification	IEC 61 439-1/-2 IEC 61 641
Dimensions	Width: 400 mm Height: 2,200 mm Depth: 600 mm
Packs of	1 pc(s).
Net weight	36
Gross weight	38.5
PCF per pack (cradle-to-gate)	106.4 kg CO ₂ eq (Cat B)
Note on PCF category	Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared
Customs tariff number	94032080
EAN	4028177929739

Features

ETIM 9 EC000261

ECLASS 8.0 27180101

Approvals

Certificates Surface finish

Explanations Declaration of conformity UK