

Rittal – The System.

Faster – better – everywhere.



SK 3124.100 Master/slave cable

State: 2/07/2026 (Source: rittal.com/nz-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SK 3124.100 - Master/slave cable for SK BUS system

The SK BUS system allows several cooling units and air/water heat exchangers with e-Comfort controller to communicate with one another. The master/slave assembly ensures an optimum operating result for complex bayed enclosure systems.

Features

| | |
|--------------------------|--|
| Model No. | SK 3124.100 |
| Product description | The SK BUS system allows several cooling units and air/water heat exchangers with e-Comfort controller to communicate with one another Master-slave configuration for complex bayed enclosure systems, for optimum operating results. |
| Technical specifications | The master-slave layout facilitates common activation and deactivation via door limit switches, parallel activation and deactivation via a temperature setpoint, and common collective fault signals and temperature logging, eliminating the need for intricate wiring. |
| Supply includes | 3 m shielded interface cable Operating instructions on programming the cooling units |
| Packs of | 1 pc(s). |
| Note | $nB = nK - 1$ nB: Number of order units (SK BUS system) nK: Number of cooling units to be linked |
| Net weight | 0.15 kg |
| Gross weight | 0.221 kg |
| Customs tariff number | 85444290 |
| ETIM 9 | EC002620 |
| ETIM 8 | EC002620 |
| ECLASS 8.0 | 27189261 |
| Product description | SK Master/slave cabel, for SK BUS system |