

Faster – better – everywhere.





SK 3243.400 Blue e+ outlet filter

POWER DISTRIBUTION >> CLIMATE CONTROL

State: 8/09/2025 (Source: rittal.com/nz-en)



IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

ENCLOSURES

SK 3243.400 - Blue e+ outlet filter EMC

The outlet filter is used in conjunction with the corresponding fan-and-filter unit to dissipate heat loss from enclosures, ventilate the enclosure and protect temperature-sensitive components. This is achieved through the direct infeed of ambient air, the temperature of which must be lower than the permissible internal temperature of the enclosure.



Features

Model No.	SK 3243.400
Design	wall-mounted
	EMC
Benefits	Easy filter changes, thanks to a new opening mechanism on the
	louvred grille
	Faster installation on the enclosure with optimised detent hooks
	Tool-free assembly
0	
Colour	RAL 7035
Supply includes	Outlet filter
	EMC filter mat
Mounting cut-out	Cut-out width: 292 mm
	Cut-out height: 292 mm
To fit Model No.	SK 3243.8xx/3244.8xx/3245.8xx
Dimensions	Width: 323 mm
	-
	Height: 323 mm Depth: 44.7 mm

Features

Protection category NEMA	Type 12 with chopped-fibre filter Type 3, 3R, 4, 4X with chopped-fibre filter and hose-proof hood
IP protection category to IEC 60 529	IP 54 with chopped-fibre filter IP 56 with chopped-fibre filter and hose-proof hood
Packs of	1 pc(s).
Net weight	0.94
Gross weight	0.941
Customs tariff number	39269097
EAN	4028177998315
ETIM 9	EC002513
ETIM 8	EC002513
ECLASS 8.0	27180706

Approvals

Approvals

UL + C-UL - FTTA UR + C-UR (recognized)