

Faster – better – everywhere.





## AS 4050.749 Wire end ferrules

State: 8/09/2025 (Source: rittal.com/nz-en)



\_\_\_\_\_

POWER DISTRIBUTION X CLIMATE CONTROL X IT INFRASTRUCTU

IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

ENCLOSURES

## AS 4050.749 - Wire end ferrules on a reel

With plastic collar.

## Features

Model No.	AS 4050.749	
Design	for wire processing machines	
Product description	With plastic collar.	
Technical specifications	Heat-resistant to 105 °C	
Material	E-Cu, galvanic tin-plated Plastic collar: Polypropylene	
Colour	Black	
To fit	Enclosure type: Crimping machine RC Crimping machine R8 Crimping machine R8 E	
Length	8 mm	
AWG	16	
Internal diameter	3.5 mm	
For cross-section	1.5 mm²	
DIN colour code	Yes	
Note	UL-certified in conjunction with the relevant tools, such as crimping machines.	
Delivery form	Taped	
Packs of	5,000 pc(s).	
Net weight	5	
Gross weight	0.722	
Customs tariff number	85369010	
EAN	4028177805170	
ETIM 9	EC00005	

## Features

ETIM 8	EC000005	
ECLASS 8.0	36659290	
Approvals		
Approvals	UL + C-UL (listed)	
Approvais		

UR