Rittal – The System.

Faster – better – everywhere.





TS 4166.000 Captive nuts

State: 16/07/2025 (Source: rittal.com/nz-en)



TS 4166.000 - Captive nuts

Used on enclosures and rails with rectangular system punching $12.5 \times 10.5 \text{ mm}$ with compression spring, designed as an insertion aid for reliable mechanical and electrical connection in the system punchings.



Features

Model No.	TS 4166.000
Product description	The compression spring, designed as an insertion aid, ensures reliable mechanical and electrical connection in the system punchings.
Installation options	On the vertical TS, VX SE enclosure section via adaptor rails for VX compatibility
	On the horizontal TS enclosure section
	On the horizontal VX SE enclosure section, bottom
	On the horizontal VX SE enclosure section, top in the depth
	On punched rails 23 x 23 mm
	On punched section without mounting flange, 23 x 73 mm
	On punched section without mounting flange, 45 x 88 mm
	On punched sections with mounting flanges, 23 x 73 mm
	On enclosures and rails with rectangular system punching 12.5 x
	10.5 mm.
Dimensions	Thread: M5
Thread	M5
Packs of	50 pc(s).
Net weight	0.4
Gross weight	0.474

© Rittal 2025 2

Features

Customs tariff number	73181692
EAN	4028177641815
ETIM 9	EC002358
ETIM 8	EC002358
ECLASS 8.0	23110815

© Rittal 2025 3