

Faster - better - everywhere.





- 4

State: 4/09/2025 (Source: r ttal.com/nz-en)

ENCLOSURES

POWER DISTRIBUTION CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES

2



FRIEDHELM LOH GROUP

VX 5301.244 - Side panel, vertically divided for VX IT

Side panels, vertically divided, for VX IT



Features

Model No.	VX 5301.244
Benefits	Easy to use
	Easy to close with snap fasteners
	Optimum access to all installed components
	Opening is only possible via internal locking elements, which
	requires free access via the doors, but significantly increases
	access security
	Individual side parts may be completely dismantled at any time without the need for tools
Material	Sheet steel
Surface finish	Powder-coated
Colour	RAL 7035
Supply includes	2 side parts
	Punched rail
	6 Hinges
	4 quick-release fasteners
	Assembly parts
Assembly instruction	Access via the front and rear doors must be guaranteed
To fit	Enclosure type: VX IT
	Height: = 2,200 mm
	Depth: = 1,000 mm

Features

IP protection category to IEC 60 529	IP 20
Basic material	Sheet steel
Packs of	1 pc(s).
Net weight	30.6
Gross weight	30.8
PCF per pack (cradle-to-gate)	117.3 kg CO2 eq (Cat B)
Note on PCF category	Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared
EAN	4028177955851
E-Number Sweden	E7282559
ETIM 9	EC002524
ECLASS 8.0	27182101