Rittal – The System.

Faster – better – everywhere.





TS 8215.500 Baying systems TS 8

State: 4/11/2025 (Source: rittal.com/nz-en)



TS 8215.500 - Baying systems TS 8

The TS 8 sheet steel baying system, with its symmetrical profile in the width and depth, offers a significant space gain, plus simple interior installation. This likewise ensures bayability from all sides. Additionally, the integral, automatic potential equalisation of all enclosure panels and the triple surface treatment ensure optimum safety.



Features

Model No.	TS 8215.500
Material	Enclosure frame: Sheet steel, 1.5 mm
	Roof: Sheet steel, 1.5 mm
	Door: Sheet steel, 2.0 mm
	Rear panel: Sheet steel, 1.5 mm
	Gland plates: Sheet steel, 1.5 mm
	Mounting plate: Sheet steel, 3.0 mm
Surface finish	Enclosure frame: Dipcoat-primed
	Door, roof and rear panel: Dipcoat-primed, powder-coated on the
	outside, textured paint
	Mounting plate and gland plates: Zinc-plated
Colour	RAL 7035

© Rittal 2025 2

Features

Enclosure frame
Door(s)
R/h door hinge with single-door enclosures, may be swapped to
opposite side
Roof plate
Rear panel
4 eyebolts
Lock: 3 mm double-bit
Gland plates
Mounting plate
2 TS punched rails 18 x 38 mm
Width: 1,200 mm
Height: 1,200 mm
Depth: 500 mm
1,099 mm x 1,096 mm
IP 55
NEMA 1
NEMA 12
Type 1
Type 12
IK09
2
Sheet steel
1 pc(s).
132
140
4000177500040
4028177522848
EC000261

© Rittal 2025 3

Approvals

Approvals	Bureau Veritas Lloyds Register of Shipping UL + C-UL (listed)
Certificates	Surface finish
Explanations	Manufacturer's declaration
	Declaration of conformity
	Declaration of conformity UK

© Rittal 2025