Rittal - The System.

Faster – better – everywhere.





RX 9362.030 RiLineX NH fuse-switch disconnector

State: 10/11/2025 (Source: rittal.com/nz-en)



RX 9362.030 - RiLineX NH fuse-switch disconnector

RiLineX NH fuse-switch disconnector in size 00 for 60 mm busbar systems. The cover can be locked and prepared for a lead seal. It also has visual fuse monitoring. Integrated measuring points on the cover ensure safe voltage testing. NH fuse-switch disconnectors have a park position to make maintenance easier. Box terminal connection to connect round conductors ranging from min. 1.5 to max. 95 mm². Cable outlet can be at the top or bottom, as required.



Features

Model No.	RX 9362.030
Benefits	Cover: can be locked and prepared for a lead seal Voltage test through separate opening
	Snap-on mounting up to 250 A and simple adjustment to busbar
	thickness 5/10 mm
	Tool-free changeover of the cable outlet
	Park position for simpler maintenance work
	All variants also available with electronic fuse monitoring
Material	Polyamide (PA 6)
	Fire protection corresponding to UL 94
	Contact tracks: Electrolytic copper, silver-plated
Colour	RAL 9005
	RAL 35745
For bar systems with centre-to-	60 mm
centre spacing	
Cable outlet	Top/bottom
Type of electrical connection	Box terminal
Rated insulation voltage	1,000 V
Rated operating current max.	160 A

© Rittal 2025 2

Features

Rated operating voltage	690 V AC
For NH size	00
Test specification	IEC/DIN EN 60 947-3 DIN EN 60 269-2 (fuse inserts)
Dimensions	Width: 106 mm Height: 195 mm Depth: 105 mm
Operating temperature range	-5 °C35 °C
Storage temperature range	-25 °C70 °C
To fit busbars	15 x 5/10 20 x 5/10 30 x 5/10
To fit busbar system	RiLineX RiLine60
Number of poles	3-pole
Utilisation category	AC-23B (400 V/100 A) AC-22B (500 V/100 A) DC-22B (250 V/100 A)
Contamination level	3
IP protection category to IEC 60 529	IP 2XB
Fire load	14.2 MJ/m²
Connection of round conductors, fine wire with AWG wire end ferrule	1.5 - 95 - 1.5 - 95 - mm²
Connection of round conductors, fine wire without wire end ferrule	1.5 - 95 mm²
Connection of round conductors, fine wire with wire end ferrule	1.5 - 95 mm²
Power dissipation (max.)	22 W
Packs of	1 pc(s).
Net weight	0.946

© Rittal 2025 3

Features

Gross weight	1.039
Copper weight (kg per piece)	0.409
Customs tariff number	85369095
ETIM 9	EC001040

Approvals

Explanations Declaration of conformity

© Rittal 2025 4