

Rittal – The System.

Faster – better – everywhere.



SV 9676.007

Spacer

State: 11/05/2026 (Source: rittal.com/nz-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SV 9676.007 - Spacer

When using smaller busbar widths, the spacer piece should be inserted into the chambers of the support to compensate for width differences.

Features

| | |
|----------------------------------------------------|-----------------------------------------------------------------------------------------------|
| Model No. | SV 9676.007 |
| Position of the bar system in the functional space | 2 1 2 |
| Note | At a bar width of < 60 mm for Flat-PLS 60 or < 100 mm for Flat-PLS 100, spacers must be used. |
| To fit busbar system | Flat-PLS 60 Flat-PLS 100 |
| To fit busbars | Flat copper busbars Flat copper busbars Flat copper busbars |
| To fit busbars | Width: 40, 50, 80 Height: 10, 10, 10 mm |
| Packs of | 16 pc(s). |
| Net weight | 0.064 kg |
| Gross weight | 0.081 kg |
| Customs tariff number | 73269098 |
| ETIM 9 | EC001900 |
| ECLASS 8.0 | 27400613 |
| Product description | SV Spacer, for busbar support, SV 9676002/004/020/21, for busbar WH: 40/50/80x10 mm |

Approvals

Approvals

Approvals

ABS

DNV

Lloyds Register