### Rittal - The System.

Faster – better – everywhere.





# SK 3145.000 Tangential fans for 482.6 mm (19")

State: 21/10/2025 (Source: rittal.com/ro-ro)



# SK 3145.000 - Tangential fans for 482.6 mm (19") Air throughput 320 m³/h

2 U tangential fan with up to 320 m3/h air throughput. The minimal noise generation of 52 dB makes it suitable for use in office environments.

#### **Features**

Model No.	SK 3145.000
Product description	Centrifugal fans for direct installation in the 482.6 mm (19") level have a wide column plus favourable noise characteristics to set them apart from other fans.
Colour	RAL 9005
Supply includes	Fully wired unit ready for connection Filter mat
Speed	2.245 rpm
Rated operating voltage	115 V, 1~, 50 Hz/60 Hz
Power consumption Pel	At 50 Hz: 37 W At 60 Hz: 46 W
Rated current max.	At 50 Hz: 0.32 A
Dimensions	Width: 482.6 mm Height: 88 mm Depth: 158 mm
Noise level	At 50 Hz: 52 dB(A) At 60 Hz: 62 dB(A)
Maximum static pressure difference	65 - 70 Pa
Operating temperature range	-10 °C55 °C
Internal circuit at 50 Hz	320 m³/h
Internal circuit at 60 Hz	330 m³/h
Packs of	1 pc(s).

© Rittal 2025 2

## **Features**

Net weight	2.3
Gross weight	2.388
Customs tariff number	84145915
EAN	4028177037151
ETIM 9	EC000320
ETIM 8	EC000320
ECLASS 8.0	27180716

# **Approvals**

Explanations Declaration of conformity

© Rittal 2025 3